# FireFighter® 410Series

LSZH Single Pair Shielded IEC60332-1 600V



## **Application**

A range of shielded single pair cables for indoor use in instrumentation, data and audio applications where protection against electrical interference is required. Cables with polyethylene (PE) insulation such as these present lower signal loss. These cables use FireFighter® Low Smoke Zero Halogen performance materials.

### Cable Design

Conductor Stranded tinned copper wire

Insulation Polyethylene (PE)

No. of Pairs 1 (1x2xAWG) Colour coded - Black / White

Drain Wire Stranded tinned copper wire
Overall Shield Overall Aluminium/Polyester tape

Outer Jacket LSZH FireFighter® SHF-1

#### Characteristics

Colour Grey RAL 7001

Rated Voltage 600 V

Temperature Range -20°C up to +90°C

### Fire Behaviour

Flame Retardant acc. to IEC 60332-1

Halogen Free acc. to IEC 60754

- Smoke Emission acc. to IEC 61034

Euroclass Eca







# FireFighter® 410Series

LSZH Single Pair Shielded IEC60332-1 600V

## Specification

		I	
Part Number	Formation	Nom. Ø	Weight
	N° x Pair x AWG	mm [±10%]	kg/km
4101P2224	1 x 2 x 22 awg	5,10	26
4101P2024	1 x 2 x 20 awg	5,18	33
4101P1824	1 x 2 x 18 awg	6,00	45
4101P1624	1 x 2 x 16 awg	7,95	60
4101P1424	1 x 2 x 14 awg	9,02	106
4101P1224	1 x 2 x 12 awg	10,16	142

### **Electrical Characteristics**

Part Number	Nom. Capacitance	Nom. Capacitance	Nom. Conductor
	(cond./cond.)	(cond./cond./scrn)	DC Resistance
	pF/m	pF/m	Ω/km
4101P2224	72,6	140	54
4101P2024	84	155	33
4101P1824	90	166	23
4101P1624	75	139	14,5
4101P1424	77	144	9,7
4101P1224	82,5	161	5,3

Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.

