

Product list

effective : 1/3/24

LSZH-FR / HFT Low Smoke Zero Halogen - Flame Retardant Electrical Conduits & Fittings

Maser NZ Ltd,
6A Piermark Dr.
Albany Auckland

Tel: 09 414 0330
Email: sales@maser.co.nz
Web: www.maser.co.nz

MASER
COMMUNICATIONS



ISO 9001 ISO 14001

Enviro Conduit

In accordance with AS/NZS 2053:2001, BS EN 61386-21, IEC 60423
All conduits are plain-ends.



Medium Duty
U.V. Stabilisers
Coloured Light Grey
LSZH-FR / HFT

Code	Size	O.D.mm x I.D.mm	Length
HFTE1	20mm	20 x 16.4	4m
HFTE2	25mm	25 x 21.4	4m
HFTE3	32mm	32 x 27.8	4m
HFTE4	40mm	40 x 35.2	4m
HFTE5	50mm	50 x 44.4	4m
HFTE6	63mm	63 x 57	4m
HFTE8	80mm	90 x 83	4m
HFTE9	100mm	114 x 104.5	4m
HFTE10	125mm	140 x 129.5	4m
HFTE11	150mm	160 x 147.4	4m

Standard Conduit

In accordance with AS/NZS 2053:2001, BS EN 61386-21, IEC 60423
All conduits are plain-ends.



Medium Duty
Long Term U.V.
Coloured Black
LSZH-FR / HFT

Code	Size	O.D.mm x I.D.mm	Length
HFTS1	20mm	20 x 16.4	4m
HFTS2	25mm	25 x 21.4	4m
HFTS3	32mm	32 x 27.8	4m
HFTS4	40mm	40 x 35.2	4m
HFTS5	50mm	50 x 44.4	4m
HFTS6	63mm	63 x 57	4m
HFTS8	80mm	90 x 83	4m
HFTS9	100mm	114 x 104.5	4m
HFTS10	125mm	140 x 129.5	4m
HFTS11	150mm	160 x 147.4	4m

Hi-Po Conduit

In accordance with AS/NZS 2053:2001, BS EN 61386-21, IEC 60423
All conduits are plain-ends.



Heavy Duty
Long Term U.V.
Coloured Black
LSZH-FR / HFT

Code	Size	O.D.mm x I.D.mm	Length
HFTH1	20mm	20 x 15.4	4m
HFTH2	25mm	25 x 20	4m
HFTH3	32mm	32 x 26.6	4m
HFTH4	40mm	40 x 33.8	4m
HFTH5	50mm	50 x 43.2	4m
HFTH6	63mm	63 x 55.2	4m
HFTH8	80mm	90 x 80.8	4m
HFTH9	100mm	114 x 101	4m
HFTH10	125mm	140 x 125	4m
HFTH11	150mm	160 x 143	4m

Orange Conduit

In accordance with AS/NZS 2053:2001, BS EN 61386-21, IEC 60423
All conduits are plain-ends.



Heavy Duty
U.V. Stabilisers
Coloured Orange
LSZH-FR / HFT

Code	Size	O.D.mm x I.D.mm	Length
HFTO1	20mm	20 x 15.4	4m
HFTO2	25mm	25 x 20	4m
HFTO3	32mm	32 x 26.6	4m
HFTO4	40mm	40 x 33.8	4m
HFTO5	50mm	50 x 43.2	4m
HFTO6	63mm	63 x 55.2	4m
HFTO8	80mm	90 x 80.8	4m
HFTO9	100mm	114 x 101	4m
HFTO10	125mm	140 x 125	4m
HFTO11	150mm	160 x 143	4m

Communications/Data Conduit

In accordance with AS/NZS 2053:2001, BS EN 61386-21, IEC 60423
All conduits are plain-ends. Also available in Heavy Duty.



Medium Duty
U.V. Stabilisers
Coloured White
LSZH-FR / HFT

Code	Size	O.D.mm x I.D.mm	Length
HFTW1	20mm	20 x 16.4	4m
HFTW2	25mm	25 x 21.4	4m
HFTW3	32mm	32 x 27.8	4m
HFTW4	40mm	40 x 35.2	4m
HFTW5	50mm	50 x 44.4	4m
HFTW6	63mm	63 x 57	4m
HFTW8	80mm	90 x 83	4m
HFTW9	100mm	114 x 104.5	4m
HFTW10	125mm	140 x 129.5	4m
HFTW11	150mm	160 x 147.4	4m

Vesda® Conduit and other aspirated smoke detection systems



Code	Colour	Size	O.D.mm x I.D.mm	Length
FDSG2	Grey	25mm	25 x 21.4	4m
FDSB2	Black	25mm	25 x 21.4	4m

Printed "FIRE DETECTION SYSTEM - DO NOT PAINT"
Conduit is produced with a red stripe along entire length.

Corrugated Conduit



- LSZH-FR / HFT
- Split conduit available upon request
- Medium Duty
- Heavy Duty available upon request

Size	Roll Lgth	Grey	Black	Orange	White
20mm	50m	HFTCOR-G-20/50	HFTCOR-B-20/50	HFTCOR-O-20/50	HFTCOR-W-20/50
25mm	50m	HFTCOR-G-25/50	HFTCOR-B-25/50	HFTCOR-O-25/50	HFTCOR-W-25/50
32mm	25m	HFTCOR-G-32/25	HFTCOR-B-32/25	HFTCOR-O-32/25	HFTCOR-W-32/25
40mm	25m	HFTCOR-G-40/25	HFTCOR-B-40/25	HFTCOR-O-40/25	HFTCOR-W-40/25
50mm	25m	HFTCOR-G-50/25	HFTCOR-B-50/25	HFTCOR-O-50/25	HFTCOR-W-50/25
63mm	10m	HFTCOR-G-63/10	HFTCOR-B-63/10	HFTCOR-O-63/10	HFTCOR-W-63/10
80mm	10m	HFTCOR-G-80/10	HFTCOR-B-80/10	HFTCOR-O-80/10	HFTCOR-W-80/10
100mm	10m	HFTCOR-G-100/10	HFTCOR-B-100/10	HFTCOR-O-100/10	HFTCOR-W-100/10

Round Junction Boxes

One Way Junction Box



Size	Grey	Black	Orange	White
20mm	EJB120	FRJB120	OJB120	WJB120
25mm	EJB125	FRJB125	OJB125	WJB125

Deep Junction Box

Size	Grey	Black	Orange	White
20mm	EDJB120	FRDJB120	ODJB120	WDJB120
25mm	EDJB125	FRDJB125	ODJB125	WDJB125

Two Way Junction Box (straight)



Size	Grey	Black	Orange	White
20mm	EJB2T20	FRJB2T20	OJB2T20	WJB2T20
25mm	EJB2T25	FRJB2T25	OJB2T25	WJB2T25

Deep Junction Box

Size	Grey	Black	Orange	White
20mm	EDJB2T20	FRDJB2T20	ODJB2T20	WDJB2T20
25mm	EDJB2T25	FRDJB2T25	ODJB2T25	WDJB2T25

Two Way Junction Box (angle)



Size	Grey	Black	Orange	White
20mm	EJB2A20	FRJB2A20	OJB2A20	WJB2A20
25mm	EJB2A25	FRJB2A25	OJB2A25	WJB2A25

Deep Junction Box

Size	Grey	Black	Orange	White
20mm	EDJB2A20	FRDJB2A20	ODJB2A20	WDJB2A20
25mm	EDJB2A25	FRDJB2A25	ODJB2A25	WDJB2A25

Round Junction Boxes

Three Way Junction Box



Size	Grey	Black	Orange	White
20mm	EJB320	FRJB320	OJB320	WJB320
25mm	EJB325	FRJB325	OJB325	WJB325

Deep Junction Box

Size	Grey	Black	Orange	White
20mm	EDJB320	FRDJB320	ODJB320	WDJB320
25mm	EDJB325	FRDJB325	ODJB325	WDJB325

Four Way Junction Box



Size	Grey	Black	Orange	White
20mm	EJB420	FRJB420	OJB420	WJB420
25mm	EJB425	FRJB425	OJB425	WJB425

Deep Junction Box

Size	Grey	Black	Orange	White
20mm	EDJB420	FRDJB420	ODJB420	WDJB420
25mm	EDJB425	FRDJB425	ODJB425	WDJB425

Deep Junction Box Extension



Size	Grey	Black	Orange	White
20-25mm	EJB26	FRJB26	OJB26	WJB26

Adaptable Box



Size	Grey	Black	Orange	White
77 x 77 x 54	EAB77	FRAB77	OAB77	WAB77
IP67 Gasket	G77			
108 x 108 x 76	EAB108	FRAB108	OAB108	WAB108
IP67 Gasket	G108			
138 x 75 x 38	EAB138	FRAB138	OAB138	WAB138
75 x 75 x 38	EAB75	FRAB75	OAB75	WAB75

Square Junction Boxes

One Way Junction Box



Size	Grey	Black	Orange	White
20mm	EJB77120	FRJB77120	OJB77120	WJB77120
25mm	EJB77125	FRJB77125	OJB77125	WJB77125
32mm	EJB132	FRJB132	OJB132	WJB132
40mm	EJB140	FRJB140	OJB140	WJB140
50mm	EJB150	FRJB150	OJB150	WJB150

Two Way Junction Box (straight)



Size	Grey	Black	Orange	White
20mm	EJB772T20	FRJB772T20	OJB772T20	WJB772T20
25mm	EJB772T25	FRJB772T25	OJB772T25	WJB772T25
32mm	EJB2T32	FRJB2T32	OJB2T32	WJB2T32
40mm	EJB2T40	FRJB2T40	OJB2T40	WJB2T40
50mm	EJB2T50	FRJB2T50	OJB2T50	WJB2T50

Two Way Junction Box (angle)



Size	Grey	Black	Orange	White
20mm	EJB772A20	FRJB772A20	OJB772A20	WJB772A20
25mm	EJB772A25	FRJB772A25	OJB772A25	WJB772A25
32mm	EJB2A32	FRJB2A32	OJB2A32	WJB2A32
40mm	EJB2A40	FRJB2A40	OJB2A40	WJB2A40
50mm	EJB2A50	FRJB2A50	OJB2A50	WJB2A50

Three Way Junction Box



Size	Grey	Black	Orange	White
20mm	EJB77320	FRJB77320	OJB77320	WJB77320
25mm	EJB77325	FRJB77325	OJB77325	WJB77325
32mm	EJB332	FRJB332	OJB332	WJB332
40mm	EJB340	FRJB340	OJB340	WJB340
50mm	EJB350	FRJB350	OJB350	WJB350

Four Way Junction Box



Size	Grey	Black	Orange	White
20mm	EJB77420	FRJB77420	OJB77420	WJB77420
25mm	EJB77425	FRJB77425	OJB77425	WJB77425
32mm	EJB432	FRJB432	OJB432	WJB432
40mm	EJB440	FRJB440	OJB440	WJB440
50mm	EJB450	FRJB450	OJB450	WJB450

Switch Boxes

Double Switch Box



Size 138 x 75 x 38

Size	Grey	Black	White
No Knockouts	LSB-P-G	LSB-P-B	LSB-P-W
20mm	LSB-20-G	LSB-20-B	LSB-20-W
25mm	LSB-25-G	LSB-25-B	LSB-25-W

Single Switch Box



Size 75 x 75 x 38

Size	Grey	Black	White
No Knockouts	SSB-P-G	SSB-P-B	SSB-P-W
20mm	SSB-20-G	SSB-20-B	SSB-20-W
25mm	SSB-25-G	SSB-25-B	SSB-25-W

Switch Box Lids

Single



Double



Size	Grey	Black	White
Single	SSB-LID-G	SSB-LID-B	SSB-LID-W
Double	LSB-LID-G	LSB-LID-B	LSB-LID-W

Fittings

Expansion Coupling



Size	Grey	Black	Orange	White
20mm	EEX20	FREX20	OEX20	WEX20
25mm	EEX25	FREX25	OEX25	WEX25
32mm	EEX32	FREX32	OEX32	WEX32
40mm	EEX40	FREX40	OEX40	WEX40
50mm	EEX50	FREX50	OEX50	WEX50
63mm	EEX63	FREX63	OEX63	WEX63
80mm	EEX80	FREX80	OEX80	WEX80
100mm	EEX100	FREX100	OEX100	WEX100
125mm	EEX125	FREX125	OEX125	WEX125
150mm	EEX150	FREX150	OEX150	WEX150

Reducing Coupling



Size	Grey	Black	Orange	White
25-20mm	ERC2520	FRRC2520	ORC2520	WRC2520
32-20mm	ERC3220	FRRC3220	ORC3220	WRC3220
32-25mm	ERC3225	FRRC3225	ORC3225	WRC3225

Fittings

Threaded Adaptor Male with Lock Nut



Size	Grey	Black	Orange	White
20mm	EMA20	FRMA20	OMA20	WMA20
25mm	EMA25	FRMA25	OMA25	WMA25
32mm	EMA32	FRMA32	OMA32	WMA32
40mm	EMA40	FRMA40	OMA40	WMA40
50mm	EMA50	FRMA50	OMA50	WMA50
63mm	EMA63	FRMA63	OMA63	WMA63

Threaded Adaptor Female



Size	Grey	Black	Orange	White
20mm	EFA20	FRFA20	OFA20	WFA20
25mm	EFA25	FRFA25	OFA25	WFA25
32mm	EFA32	FRFA32	OFA32	WFA32

Bush for Threaded Adaptor



Size	Grey	Black	Orange	White
20mm	TB20-G	TB20-B	TB20-O	TB20-W
25mm	TB25-G	TB25-B	TB25-O	TB25-W

Inspection Elbow



Size	Grey	Black	Orange	White
20mm	EIE20	FRIE20	OIE20	WIE20
25mm	EIE25	FRIE25	OIE25	WIE25
32mm	EIE32	FRIE32	OIE32	WIE32
40mm	EIE40	FRIE40	OIE40	WIE40
50mm	EIE50	FRIE50	OIE50	WIE50

Inspection Tee



Size	Grey	Black	Orange	White
20mm	EIT20	FRIT20	OIT20	WIT20
25mm	EIT25	FRIT25	OIT25	WIT25
32mm	EIT32	FRIT32	OIT32	WIT32
40mm	EIT40	FRIT40	OIT40	WIT40
50mm	EIT50	FRIT50	OIT50	WIT50

Fittings

Sweep Bend



Size	Grey	Black	Orange	White
20mm	ESB20	FRSB20	OSB20	WSB20
25mm	ESB25	FRSB25	OSB25	WSB25
32mm	ESB32	FRSB32	OSB32	WSB32

Note: For sizes above 32mm please refer to our Smart-Bend™ which will cover sizes 40mm-150mm

Sweep Bend 22.5°



600mm Radius

Size	Grey	Black	Orange	White
100mm	ESB100-22.5	FRSB100-22.5	OSB100-22.5	WSB100-22.5

End Caps



Size	Grey	Black	Orange	White
20mm	ECAP20	FRCAP20	OCAP20	WCAP20
25mm	ECAP25	FRCAP25	OCAP25	WCAP25
32mm	ECAP32	FRCAP32	OCAP32	WCAP32
40mm	ECAP40	FRCAP40	OCAP40	WCAP40
50mm	ECAP50	FRCAP50	OCAP50	WCAP50
63mm	ECAP63	FRCAP63	OCAP63	WCAP63
90mm	ECAP80	FRCAP80	OCAP80	WCAP80
100mm	ECAP100	FRCAP100	OCAP100	WCAP100
125mm	ECAP125	FRCAP125	OCAP125	WCAP125
150mm	ECAP150	FRCAP150	OCAP150	WCAP150

Coupling



Size	Grey	Black	Orange	White
20mm	EC20	FRC20	OC20	WC20
25mm	EC25	FRC25	OC25	WC25
32mm	EC32	FRC32	OC32	WC32
40mm	EC40	FRC40	OC40	WC40
50mm	EC50	FRC50	OC50	WC50
63mm	EC63	FRC63	OC63	WC63
80mm	EC80	FRC80	OC80	WC80
100mm	EC100	FRC100	OC100	WC100
125mm	EC125	FRC125	OC125	WC125
150mm	EC150	FRC150	OC150	WC150

Fittings & Accessories

Pit Bush / Bell Mouth



Pit Bush

Size	Grey	Black	Orange	White
100mm	EPB100	FRPB100	OPB100	WPB100

Bell Mouth



Size	Grey	Black	Orange	White
100mm	EBM100	FRBM100	OBM100	WBM100

Support Clips



20-40mm



50-100mm

Size	Grey	Black	White
20mm	C20E	C20FR	C20W
25mm	C25E	C25FR	C25W
32mm	C32E	C32FR	C32W
40mm	C40E	C40FR	C40W
50mm	C50E	C50FR	C50W
63mm	C63E	C63FR	C63W
80mm	C80E	C80FR	C80W
100mm	C100E	C100FR	C100W

Adhesive



Code	Description
AG-50	Applicator Gun
EVA-50 MN	Mixing Nozzle
EVA-50	Adhesive

Application Rate

Adhesive qty applied at a 3-5mm bead for each conduit size

Size	Applications
20	78
25	64
32	50
40	40
50	31
63	26
80	17
100	14
125	12
150	10


Smart Bend™

Evcco Smart Bend™ offers a unique approach to conduit bends through individual segments that “Snap-Lock” together. This concept allows bends to be assembled on site to provide various angles from 7.5 degrees to 90 degrees and beyond if necessary.

Smart-bend can be adjusted axially to provide compounded angles which are particularly important when connecting misaligned wall and floor penetrations.

Sizes range from;

40mm, 50mm, 63mm, 80mm, 100mm, 125mm & 150mm



Size	Radius
40mm	312mm
50mm	320mm
63mm	325mm
80mm	550mm
100mm	600mm
125mm	600mm
150mm	760mm

Sizes 40mm, 50mm and 63mm conduit (15° segments)

Segments required	1	2	3	4	5	6
40,50,63	15°	30°	45°	60°	75°	90°

Sizes 80mm, 100mm, 125mm and 150mm conduit (7.5° segments)

Segments required	1	2	3	4	5	6	7	8	9	10	11	12
80,100,125,150	7.5°	15°	22.5°	30°	37.5°	45°	52.5°	60°	67.5°	75°	82.5°	90°


Smart Bend™ is offered in the following configurations:

- Individual components (to be assembled by end user)
- Assembled (Snap fit assembly)
- Bonded Assembly (Adhesive or fused assembly)

Bend Component	Code	Size	Colour	Assembled Angle	Bonded
Segment	SEG	40	B (Black)	7.5	A
Socket/ Male Connector	SMC	50	W (White)	15	
Socket / Female Connector	SFC	63	O (Orange)	22.5	
Assembled Bend	SBA	80	G (Grey)	30	
		100		37.5	
		125		45	
		150		52.5	
				60	
				67.5	
				75	
				82.5	
				90	

Bends

Socket - Male Connector



Size	Black	Orange	White
40	SMC40-B	SMC40-O	SMC40-W
50	SMC50-B	SMC50-O	SMC50-W
63	SMC63-B	SMC63-O	SMC63-W
80	SMC80-B	SMC80-O	SMC80-W
100	SMC100-B	SMC100-O	SMC100-W
125	SMC125-B	SMC125-O	SMC125-W
150	SMC150-B	SMC150-O	SMC150-W

Socket - Female Connector



Size	Black	Orange	White
40	SFC40-B	SFC40-O	SFC40-W
50	SFC50-B	SFC50-O	SFC50-W
63	SFC63-B	SFC63-O	SFC63-W
80	SFC80-B	SFC80-O	SFC80-W
100	SFC100-B	SFC100-O	SFC100-W
125	SFC125-B	SFC125-O	SFC125-W
150	SFC150-B	SFC150-O	SFC150-W

Segment



Sizes: 40, 50 and 63mm



Sizes: 80, 100, 125 and 150mm

Size	Black	Orange	White
40	SEG40-B	SEG40-O	SEG40-W
50	SEG50-B	SEG50-O	SEG50-W
63	SEG63-B	SEG63-O	SEG63-W
80	SEG80-B	SEG80-O	SEG80-W
100	SEG100-B	SEG100-O	SEG100-W
125	SEG125-B	SEG125-O	SEG125-W
150	SEG150-B	SEG150-O	SEG150-W

Bends

40mm Smart-Bend™ Snap Fit Assembled or Bonded Assembly

Angle	Black	Orange	White
15°	SBA40-B-15	SBA40-O-15	SBA40-W-15
30°	SBA40-B-30	SBA40-O-30	SBA40-W-30
45°	SBA40-B-45	SBA40-O-45	SBA40-W-45
60°	SBA40-B-60	SBA40-O-60	SBA40-W-60
75°	SBA40-B-75	SBA40-O-75	SBA40-W-75
90°	SBA40-B-90	SBA40-O-90	SBA40-W-90

If Smart-Bend is required to be bonded add a “-A” to the end of code

50mm Smart-Bend™ Snap Fit Assembled or Bonded Assembly

Angle	Black	Orange	White
15°	SBA50-B-15	SBA50-O-15	SBA50-W-15
30°	SBA50-B-30	SBA50-O-30	SBA50-W-30
45°	SBA50-B-45	SBA50-O-45	SBA50-W-45
60°	SBA50-B-60	SBA50-O-60	SBA50-W-60
75°	SBA50-B-75	SBA50-O-75	SBA50-W-75
90°	SBA50-B-90	SBA50-O-90	SBA50-W-90

If Smart-Bend is required to be bonded add a “-A” to the end of code

63mm Smart-Bend™ Snap Fit Assembled or Bonded Assembly

Angle	Black	Orange	White
15°	SBA63-B-15	SBA63-O-15	SBA63-W-15
30°	SBA63-B-30	SBA63-O-30	SBA63-W-30
45°	SBA63-B-45	SBA63-O-45	SBA63-W-45
60°	SBA63-B-60	SBA63-O-60	SBA63-W-60
75°	SBA63-B-75	SBA63-O-75	SBA63-W-75
90°	SBA63-B-90	SBA63-O-90	SBA63-W-90

If Smart-Bend is required to be bonded add a “-A” to the end of code

Bends

80mm Smart-Bend™ Snap Fit Assembled or Bonded Assembly

Angle	Black	Orange	White
7.5°	SBA80-B-7.5	SBA80-O-7.5	SBA80-W-7.5
15°	SBA80-B-15	SBA80-O-15	SBA80-W-15
22.5°	SBA80-B-22.5	SBA80-O-22.5	SBA80-W-22.5
30°	SBA80-B-30	SBA80-O-30	SBA80-W-30
37°	SBA80-B-37.5	SBA80-O-37.5	SBA80-W-37.5
45°	SBA80-B-45	SBA80-O-45	SBA80-W-45
52.5°	SBA80-B-52.5	SBA80-O-52.5	SBA80-W-52.5
60°	SBA80-B-60	SBA80-O-60	SBA80-W-60
67.5°	SBA80-B-67.5	SBA80-O-67.5	SBA80-W-67.5
75°	SBA80-B-75	SBA80-O-75	SBA80-W-75
82.5°	SBA80-B-82.5	SBA80-O-82.5	SBA80-W-82.5
90°	SBA80-B-90	SBA80-O-90	SBA80-W-90

If Smart-Bend is required to be bonded add a “-A” to the end of code

100mm Smart-Bend™ Snap Fit Assembled or Bonded Assembly

Angle	Black	Orange	White
7.5°	SBA100-B-7.5	SBA100-O-7.5	SBA100-W-7.5
15°	SBA100-B-15	SBA100-O-15	SBA100-W-15
22.5°	SBA100-B-22.5	SBA100-O-22.5	SBA100-W-22.5
30°	SBA100-B-30	SBA100-O-30	SBA100-W-30
37°	SBA100-B-37.5	SBA100-O-37.5	SBA100-W-37.5
45°	SBA100-B-45	SBA100-O-45	SBA100-W-45
52.5°	SBA100-B-52.5	SBA100-O-52.5	SBA100-W-52.5
60°	SBA100-B-60	SBA100-O-60	SBA100-W-60
67.5°	SBA100-B-67.5	SBA100-O-67.5	SBA100-W-67.5
75°	SBA100-B-75	SBA100-O-75	SBA100-W-75
82.5°	SBA100-B-82.5	SBA100-O-82.5	SBA100-W-82.5
90°	SBA100-B-90	SBA100-O-90	SBA100-W-90

If Smart-Bend is required to be bonded add a “-A” to the end of code

Bends

125mm Smart-Bend™ Snap Fit Assembled or Bonded Assembly

Angle	Black	Orange	White
7.5°	SBA125-B-7.5	SBA125-O-7.5	SBA125-W-7.5
15°	SBA125-B-15	SBA125-O-15	SBA125-W-15
22.5°	SBA125-B-22.5	SBA125-O-22.5	SBA125-W-22.5
30°	SBA125-B-30	SBA125-O-30	SBA125-W-30
37°	SBA125-B-37.5	SBA125-O-37.5	SBA125-W-37.5
45°	SBA125-B-45	SBA125-O-45	SBA125-W-45
52.5°	SBA125-B-52.5	SBA125-O-52.5	SBA125-W-52.5
60°	SBA125-B-60	SBA125-O-60	SBA125-W-60
67.5°	SBA125-B-67.5	SBA125-O-67.5	SBA125-W-67.5
75°	SBA125-B-75	SBA125-O-75	SBA125-W-75
82.5°	SBA125-B-82.5	SBA125-O-82.5	SBA125-W-82.5
90°	SBA125-B-90	SBA125-O-90	SBA125-W-90

If Smart-Bend is required to be bonded add a "-A" to the end of code

150mm Smart-Bend™ Snap Fit Assembled or Bonded Assembly

Angle	Black	Orange	White
7.5°	SBA150-B-7.5	SBA150-O-7.5	SBA150-W-7.5
15°	SBA150-B-15	SBA150-O-15	SBA150-W-15
22.5°	SBA150-B-22.5	SBA150-O-22.5	SBA150-W-22.5
30°	SBA150-B-30	SBA150-O-30	SBA150-W-30
37°	SBA150-B-37.5	SBA150-O-37.5	SBA150-W-37.5
45°	SBA150-B-45	SBA150-O-45	SBA150-W-45
52.5°	SBA150-B-52.5	SBA150-O-52.5	SBA150-W-52.5
60°	SBA150-B-60	SBA150-O-60	SBA150-W-60
67.5°	SBA150-B-67.5	SBA150-O-67.5	SBA150-W-67.5
75°	SBA150-B-75	SBA150-O-75	SBA150-W-75
82.5°	SBA150-B-82.5	SBA150-O-82.5	SBA150-W-82.5
90°	SBA150-B-90	SBA150-O-90	SBA150-W-90

If Smart-Bend is required to be bonded add a "-A" to the end of code

