



MAS2C15LSZH

2 Core 1.5mm² Tinned Copper Lighting Control Cable

Low Smoke Zero Halogen (LSZH)

AS/NZS 5000.2:2006 450/750V



Part number	MAS2C15LSZH
Pair Count	2 Core
Conductor	Tinned Copper Wire
Size	1.5mm ²
Stranding	19/0.32mm
Insulation	HFI-90-TP Low Smoke Zero Halogen
Insulation Thickness	0.60mm
Core Identification	Black/Red
Outer Sheath	HFS-90-TP Low Smoke Zero Halogen - Grey
Outer Sheath Thickness	1.20mm
Cable Overall Diameter (Nominal)	8.2mm
Outer Sheath Colour	Grey
Temperature Rating °C	-25°C to +90°C
Nom. Capacitance Cond. To Cond. pF/m	70.0
Nom. Cond DC Resistance Ω/km @ 20°C	12.2
Operating Voltage	450/750V
Metre Marking	Every 1 Metre
Approx Weight kg/km	75
Packaging	250m or 500m Strong Wooden Drums
Standards	AS/NZS5000.2, AS/NSZS1125, AS/NZS3808, IEC60332-1-2
RoHS Compliant	Yes

Jacket Print

MASER MAS2C15LSZH 2C 1.5mm² TCW LSZH LIGHTING CONTROL CABLE AS/NZS5000.2 450/750V 90° (Date) (Metre Mark)

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.