TECHNICAL DATA SHEET



KNX Certified Cable (497/15174/18), Green, LSZH

EXTRA LOW VOLTAGE - NOT FOR MAIN CONNECTION







Part number	MAS1PKNX	MAS2PKNX
Pair Count	1 Pair	2 Pair
Ref:	KNX 1x2x0.8mm LSZH Green	KNX 2x2x0.8mm LSZH Green
Conductor	Solid Bare Copper	Solid Bare Copper
Size	0.8mm Ø Solid Conductor	0.8mm Ø Solid Conductor
Insulation	Polyethylene	Polyethylene
Pair Identification	Black/Red	Black/Red , White/Yellow
Twist Rate	20 per metre	20 per metre
Collective Screen	Aluminium/Polyester foil screen & 0.14mm² (7/0.16mm) tinned copper drain wire	Aluminium/Polyester foil screen & 0.14mm² (7/0.16mm) tinned copper drain wire
Outer Sheath	Low Smoke Halogen Free	Low Smoke Halogen Free
Diameter mm (nominal)	5.6	6.8
Colour	Green	Green
Operating Temperature Rating °C	-40°C to +70°C	-40°C to +70°C
Weight kg/km	44	61
Mutual Capacitance pF/m Cond. To Cond	90 pF/m	90 pF/m
Conductor Resistance D.C. Ω/km @ 20°C	37.7	37.7
Insulation Resistance MΩ.M @ 20°C	200	200
Voltage Rating	250v	250v
Bending Radius	10 x O.D	10 x O.D
Flame Retardant	IEC 60332-1-2	IEC 60332-1-2
Low Smoke Generation	IEC 61034-1&2	IEC 61034-1&2
Halogen Gas Emission	IEC 60754-1&2	IEC 60754-1&2
RoHS2 compliant	Yes	Yes
Metre Marked	Yes	Yes
Certification	497/15174/18	497/15174/18

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

