



MAS3COS18LS

3 Core 18awg (0.8mm) Overall Screen Audio/Control Cable

Low Smoke Zero Halogen (LSZH)

EXTRA LOW VOLTAGE – NOT FOR MAINS CONNECTION



Part number	MAS3COS18LS
Pair Count	3 Core
Conductor	Tinned Copper Wire
Size	18awg (0.8mm)
Stranding	7/0.40mm
Insulation	Low Smoke Zero Halogen
Insulation Thickness	0.203mm ± 0.03mm
Pair Identification	Black/Red/White
Collective Screen	Aluminium/Polyester foil screen & 24awg (7/0.20mm) tinned copper drain wire
Outer Sheath	Low Smoke Zero Halogen - Grey
Diameter mm (nominal)	4.30mm ± 0.15mm
Colour	Grey
Temperature Rating °C	-20°C to +75°C
Nom. Capacitance Cond. To Cond. pF/m	116.22
Nom. Capacitance Cond. To Scr. pF/m	209.67
Nom. Cond DC Resistance Ω/km @ 20°C	21.35
Insulation Voltage Rating	300v
Metre Marking	001m – 305m
Weight kg/305m	13.54
Packaging	305m/Reel-in-a-Box
UL Specification	CMR
UL Flame Test	UL 1666 Riser
RoHS compliant	Yes

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.