

## INSTRUMENTATION CABLES – MAS SERIES


### OVERALL SCREEN

### MAS5401CSLS – 1 Pair 0.75mm<sup>2</sup> TCW CS LSZH



**APPLICATION:** Low Smoke Zero Halogen Instrumentation Cable suitable for Industrial/Greenstar Applications.

<b>Standards</b>	AS/NZS1125 , AS/NZS3808 , IEC 60332-1-2 , IEC 60332-3-22 , IEC 60079.14 , <b>RoHS</b> Compliant
<b>Conductor</b>	Stranded Tinned Copper Conductor 0.75mm (7/0.37mm)
<b>Insulation</b>	0.4mm Low Smoke Zero Halogen White/Black Numbered Pair
<b>Screen</b>	Overall Shield of Al/Polyester Foil c/w Tinned Copper Drain Wire (7/0.20mm)
<b>Armour</b>	Not Applicable
<b>Sheath</b>	Low Smoke Zero Halogen - Black
<b>Operating Temp.</b>	-20°C to +90°C
<b>Max. Rated Voltage</b>	110VRMS/150VDC
<b>Insulation Voltage Rating</b>	300V
<b>Max. Current Rating</b>	7.5 Amp
<b>Max. DC Resistance @ 20°C</b>	24.5 Ω/km
<b>Max. Capacitance Cond. To Cond. (Screened)</b>	120pf/m
<b>Max. Capacitance Cond. To Scr. (Screened)</b>	220pf/m
<b>Inductance @ 1kHz</b>	0.98 mH/km
<b>L/R Ratio @ 1kHz</b>	20.0 μH/Ω
<b>Insulation Resistance</b>	140 MΩ/km
<b>Bending Radius (Fixed)</b>	10D (D = Cable Diameter)



Product	Pairs	Conductor	Insulation Thickness	Outer Sheath Thickness	Approx Cable O.D	Approx. Cable Weight
<b>Maser Ordering Code</b>	<b>Number of Pairs</b>	<b>mm<sup>2</sup></b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>Kg/km</b>
MAS5401CSLS	1 Pair	0.75mm	0.40	0.80	5.7	45

#### Jacket Marking

MASER MAS5401CSLS INSTRUMENTATION CABLE 1PR 0.75mm<sup>2</sup> TCW/LSZH/CS/LSZH V90 UV RoHS (MANUFACTURE DATE) (METRE MARK)

**Recommended Gland = MM-A1A2-20S16**

**Disclaimer:** Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.