TECHNICAL DATA SHEET





INSTRUMENTATION CABLES – MAS SERIES OVERALL SCREEN - STEEL WIRE ARMOURED INTRINSICALLY SAFE

MAS5524CSSWA BLUE - 24 Pair 1.5mm² TCW CS SWA

APPLICATION: Instrumentation Cable suitable for intrinsically safe applications requiring mechanical protection. Suitable for Direct Burial.

Standards	AS/NZS1125 , AS/NZS3808 ,			
	IEC 60332-1-2 , IEC 60332-3-22 ,			
	IEC 60079.14 , RoHS Compliant			
Conductor	Stranded Tinned Copper Conductor			
	1.5mm (7/0.50mm)			
Insulation	0.4mm PVC ,V90HT ,			
	White/Black Numbered Pair's			
Screen	Overall Shield of Ali/Polyester Foil c/w			
	Tinned Copper Drain Wire (7/0.20mm)			
Armour	Galvanized Steel Wire			
Sheath	SPVC , 5V-90 , Flame Retardant ,			
	UV Resistant Blue PVC Intrinsically Safe			
Operating Temp.	-20°C to +90°C			
Rated Voltage	110VRMS/150VDC			
Insulation Voltage Rating	300V			
Max. Current Rating	13 Amp			
Max. DC Resistance @ 20°C	13.6 Ω/km			
Max. Capacitance Cond. To	200 pF/m			
Cond. (Screened)				
Max. Capacitance Cond. To	300 pF/m			
Scr. (Screened)				
Inductance @ 1kHz	0.95 mH/km			
L/R Ratio @ 1kHz	36.5 μΗ/Ω			
Insulation Resistance	140 MΩ/km			
Bending Radius (Fixed)	10D (D = Cable Diameter)			





Product	Pairs	Conductor	O.D over Bedding	GSWA Size	O.D over Armour	Outer Sheath Thickness	Nominal Cable O.D	Cable Weight
Maser Ordering Code	Number of Pairs	mm²	mm	mm	mm	mm	mm	Kg/km
MAS5524CSSWA BLUE	24 Pair	1.5mm	24.2	1.6	27.4	2.0	31.4	2042

Jacket Marking

MASER MASS524CSSWA INSTRUMENTATION CABLE 24PR 1.5mm² TCW/PVC/CS/PVC/SWA/PVC V-90 UV ROHS (MANUFACTURE DATE) (METRE MARK)

Recommended Gland = Please contact Maser

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

