

MASAFE 2 Core, Figure 8 Parallel Webbed, V90 Cable

EXTRA LOW VOLTAGE – NOT FOR MAINS CONNECTION



CONSTRUCTION	1.13mm	1.84mm
ORDERING CODE	100m = MASAFE216030 100M 250m = MASAFE216030 250M 500m = MASAFE216030 500M	100m = MASAFE226030 100M 250m = MASAFE226030 250M 500m = MASAFE226030 500M
CONDUCTOR	Stranded Oxygen Free Plain Copper Wire to AS1125 1.13mm (16.5 AWG) $\phi = 16/0.30 \pm 0.005\text{mm} * 2$ Voltage Rating: AC 50V / DC 120V to AS/NZS 3000:2000 Amp Rating @ 30°C: 16 Max. DC Resistance @ 20°C: 17.30 m Ω /mt	Stranded Oxygen Free Plain Copper Wire to AS1125 1.84mm (14.5AWG) $\phi = 26/0.30 \pm 0.005\text{mm} * 2$ Voltage Rating: AC 50V / DC 120V to AS/NZS 3000:2000 Amp Rating @ 30°C: 22 Max. DC Resistance @ 20°C: 10.65 m Ω /mt
INSULATION	V90 PVC to AS/NZS3191 Colour: Red with Black trace Thickness: 0.55mm	V90 PVC to AS/NZS3191 Colour: Red with Black trace Thickness: 0.55mm
NOMINAL O.D (mm)	2.45 x 5.20 $\pm 0.10\text{mm}$	2.8 x 5.90 $\pm 0.10\text{mm}$
PACKAGING	100m Plastic Reel 250m Plastic Reel 500m Plastic Reel	100m Plastic Reel 250m Plastic Reel 500m Plastic Reel



Maser Communications products are approved and meet the GREENSTAR "Best Practice PVC" criteria as set out by the Green Building Council of Australia (GBCA). BUREAU VERATIS CoC No:2821 7/8/2019. As part of this commitment to reduce the environmental impact of PVC material, Maser Communications will aid in the process of recycling any of their relevant product that has reached end of life. For further information on this process please contact us.

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.