

## INDUSTRIAL CONTROL CABLES – MASCC1\*\*/SWA SERIES

### STEEL WIRE ARMoured CIRCULAR MULTICORES

### MASCC107/1.5SWA - 7 Core 1.5mm<sup>2</sup> TCW/PVC/PVC/SWA/PVC

**APPLICATION:** For mains and sub-mains control circuits requiring mechanical protection (For fixed applications)  
Industrial and Commercial. Suitable for Direct Burial.

<b>Standards</b>	AS/NZS1125 , AS/NZS3008 ,AS/NZS3808 AS/NZS5000.1 , IEC 60332-1-2, IEC60332-3-22 , IEC 60079.14 , <b>RoHS</b> Compliant
<b>Rated Voltage</b>	0.6/1kV
<b>Conductor</b>	Stranded Tinned Copper Conductor 1.5mm <sup>2</sup> (7/0.50) Class 2
<b>Insulation</b>	0.8mm PVC V90 White Numbered Cores
<b>Seperator</b>	PET Tape or Non-Woven Tape
<b>Bedding</b>	SPVC 5V-90 Flame Retardant
<b>Armour</b>	Galvanised Steel Wire
<b>Sheath</b>	SPVC ,5V-90 ,Flame Retardant UV Resistant PVC ,Black
<b>Operating Temp.</b>	-20°C to +90°C
<b>Max. DC Resistance @ 20°C (Ω/KM)</b>	13.6
<b>Nominal Amps Unenclosed @ 30°C Fixed Touching 2 Conductor</b>	21 Amps
<b>Nominal Amps Unenclosed @ 30°C Fixed Touching 3 Conductor</b>	17 Amps
<b>Single Phase Voltage Drop 2 Conductor (@ 50Hz 90°C) mV/A.m</b>	33.0
<b>3 Phase Voltage Drop 3 Conductor (@ 50Hz 90°C) mV/A.m</b>	28.6



Product	Pairs	Conductor	O.D over Bedding	GSWA Size	O.D over GSWA	Outer Sheath Thickness	Nominal Cable O.D	Cable Weight
<b>Maser Ordering Code</b>	<b>Number of Cores</b>	<b>mm<sup>2</sup></b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>Kg/km</b>
MASCC107/1.5SWA	7 Core	1.5mm	13.4	0.9	15.2	1.8	18.8	524

#### Jacket Marking

MASER MASCC107/1.5SWA 7C 1.5mm<sup>2</sup> TCW/PVC/PVC/SWA/PVC V-90 AS/NZS5000.1 ELECTRICAL CABLE 0.6/1KV (MANF. DATE) (METRE MARK)

**Recommended Gland = MM-E1W-20L**

**Disclaimer:** Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.