


## CIRCULAR TPS POWER CABLES – MASCP\*G SERIES

### UNARMoured MULTICORE + EARTH

### MASCP3G/1.5 - 2 Core 1.5mm<sup>2</sup> + E1.5mm<sup>2</sup> TCW/PVC/PVC

**APPLICATION:** For mains and sub-mains power circuits (For fixed applications) - Industrial and Commercial

<b>Standards</b>	AS/NZS1125 , AS/NZS3008 , AS/NZS3808 AS/NZS5000.2 , IEC 60332-1-2 IEC 60079.14 , <b>RoHS</b> Compliant
<b>Rated Voltage</b>	450/750V
<b>Conductor</b>	Stranded Tinned Copper - Class 2
<b>Stranding</b>	2x1.5+E1.5 (7/0.50+7/0.50)
<b>Insulation</b>	0.6mm PVC V90
<b>Core Colours</b>	Red/Black/Green-Yellow
<b>Seperator</b>	PET Tape or Non-Woven Tape
<b>Sheath</b>	SPVC ,5V-90 ,Flame Retardant UV Resistant PVC ,Black
<b>Operating Temp.</b>	-20°C to +90°C
<b>Max. DC Resistance @ 20°C (Ω/KM)</b>	13.8
<b>Single Phase Current (A) Unenclosed @ 30°C Fixed Touching</b>	21 Amps
<b>Single Phase Voltage Drop (@ 50Hz &amp; 75°C) mV/A.m</b>	33.0



Product	Cores	Conductor	Insulation Thickness	Outer Sheath Thickness	Approx Cable O.D	Approx. Cable Weight
<b>Maser Product Code</b>	<b>Number of Cores</b>	<b>mm<sup>2</sup></b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>Kg/km</b>
MASCP3G/1.5	2C+E	2x1.5+E1.5	0.60	1.2	8.5	101

#### Jacket Marking

MASER MASCP3G/1.5 2Cx1.5mm<sup>2</sup>+E1.5mm<sup>2</sup> TCW/PVC/PVC V-90 450/750V AS/NZS5000.2 ELECTRIC CABLE (DATE) (METRE)

**Recommended Gland = MM-A1A2-20S**

**Bending Radius = 12x Cable O.D during Installation. 8 x Cable O.D Installed.**

**Disclaimer:** Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.