


VARIABLE SPEED DRIVE CABLES (VSD) – MASVSD*G SERIES UNARMOURED MULTICORES + EARTH (Split Earth for 6mm upwards) MASVSD4G10.0 - 3 Core 10.0mm² + 3E1.5mm² TCW/XLPE/PVC/AL+TCWB/PVC

APPLICATION: Suitable for use with VSD's where RFI and EMC protection is required. Fixed Installations.

Standards	AS/NZS1125 , AS/NZS3008 , AS/NZS5000.1 , IEC 60332-1-2 IEC60228 , RoHS Compliant
Rated Voltage	0.6/1kV
Conductor	Stranded Tinned Copper Class 5
Stranding	3x10.0+3xE1.5 (80/0.40+30/0.25)
Insulation	0.7mm XLPE X-90
Core Colours	Red/White/Blue/Green-Yellow
Bedding	SPVC 5V-90
Screen	100% Aluminium Foil
Screen	85% Tinned Copper Braid
Outer Sheath	SPVC , 5V-90, Flame Retardant UV Stabilised , Black
Operating Temp.	-20°C to +90°C
Max. DC Resistance @ 20°C (Ω/KM)	1.83
3 Phase Current (A) Unenclosed @ 30°C Fixed Touching	67 Amps
3 Phase Voltage Drop (@ 50Hz & 90°C) mV/A.m	4.05



Product	Cores	Conductor	Approx. O.D over Braid	Outer Sheath Thickness	Approx Cable O.D	Approx. Cable Weight
Maser Product Code	Number of Cores	mm ²	mm	mm	mm	Kg/km
MASVSD4G10.0	3C+E	3x10.0+3E1.5	16.0	1.8	20.1	841

Jacket Marking

MASER MASVSD4G10.0 3x10.0MM+3xE1.5MM TCW/XLPE/PVC/AL+TCWB/PVC X-90 AS/NZS5000.1 ELECTRICAL CABLE 0.6/1KV (MANUF DATE) (MTR)

Recommended Gland = MM-M32-25E

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.