TECHNICAL DATA SHEET

VARIABLE SPEED DRIVE CABLES (VSD) – MASVSDCTS SERIES

COPPER TAPE SCREEN

UNARMOURED MULTICORES + EARTH (Split Earth for 6mm upwards)

MASVSD4G6.0CTS - 3 Core 6.0mm² + 3E1.5mm² TCW/XLPE/PVC/CTS/PVC

APPLICATION: **Suitable for use with VSD's where RFI and EMC protection is required. Fixed Installations.**

Standards	AS/NZS1125 , AS/NZS3008 , AS/NZS5000.1 , IEC 60332-1-2 ***RoHS*** Compliant
Rated Voltage	0.6/1kV
Conductor	Class 5 Stranded Tinned Copper
Cond. Construction	3x6.0+3E1.5
Insulation	0.7mm XLPE X-90
Core Colours	Red/White/Blue/Green-Yellowx3
Bedding	SPVC 5V-90
Screen	100% Copper Tape - 20% Overlap
Outer Sheath	SPVC , 5V-90, Flame Retardant UV Stabilised , Black
Operating Temp.	-20°C to +90°C
Max. DC Resistance @ 20°C (Ω/KM)	3.39
3 Phase Current (A) Unenclosed @ 30°C Fixed Touching	47 Amps
3 Phase Voltage Drop (@ 50Hz & 90°C) mV/A.m	6.80



Product	Cores	Conductor	Approx. O.D over Copper Tape Screen	Outer Sheath Thickness	Approx Cable O.D	Approx. Cable Weight
Maser Product Code	**Number of Cores**	**mm²**	**mm**	**mm**	**mm**	**Kg/km**
MASVSD4G6.0CTS	3C+3E	3x6.0+3E1.5	13.7	1.8	17.8	491

Jacket Marking

MASER MASVSD4G6.0CTS 3Cx6.0mm² + 3E1.5mm² TCW/XLPE/PVC/CTS/PVC X-90 0.6/1KV AS/NZS5000.1 ELECTRIC CABLE (FOR FIXED APPLICATIONS ONLY) 07/2026 **M

Recommended Gland = MM-M32-20E

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

Maser Communications (NZ) Ltd
09 414 0330 | sales@maser.co.nz | www.maser.co.nz