

PRODUCT CODE: MSEC 4142/*TCWLS**



4 Core 0.44mm (14/0.2), LSZH, Tinned Copper, Security Cable

EXTRA LOW VOLTAGE – NOT FOR MAINS CONNECTION



ORDERING CODE	300m = MSEC 4142/300TCWLS
CONDUCTOR	Stranded, Tinned, Oxygen Free Plain Copper Wire to AS1125 $\varnothing = 14 \times 0.20 \pm 0.005 \text{ mm}^4$ Max. conductor DC resistance @ 20°C: 44.8 ohms/Km Amp Rating: 2.8 Capacitance Conductor to Conductor: 65 pF/m
INSULATION	LSZH (HFS-90-TP to AS3808) – Low Smoke Zero Halogen $\varnothing = 1.5 \pm 0.05 \text{ mm}^4$ Colour: Red, Blue, White, Black Thickness: 0.3mm Voltage Rating: 300V
OUTER JACKET	LSZH (HFS-90-TP to AS3808) Colour: White Thickness: 0.60mm +/- 0.05mm
NOMINAL O.D (mm)	$\varnothing = 4.5 \pm 0.10 \text{ mm}$
PACKAGING	300m Reel-in-a-Box
CABLE MARKING	MASER SECURITY SOLUTIONS MSEC4142 LSZH 0.44mm ² TCW ACA3166 SECURITY CABLE EXTRA LOW VOLTAGE DD/MM/YYYY 001M-300M

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.