TECHNICAL DATA SHEET



PRODUCT CODE: MSEC 6072SCR/***TCW

6 Core 0.22mm (7/0.2) Tinned Copper, Foil Shield, Security Cable

Suitable for RS-232 applications

EXTRA LOW VOLTAGE - NOT FOR MAINS CONNECTION



ORDERING CODE	100m = MSEC 6072SCR/100TCW 300m = MSEC 6072SCR/300TCW
	Stranded, Tinned, Oxygen Free Plain Copper Wire to AS1125 Ø =7*0.20±0.005 mm*6
CONDUCTOR	Max. conductor DC resistance @ 20°C: 89.5 ohms/Km Amp Rating: 1.4 Capacitance Conductor to Conductor: 70 pF/m Capacitance Conductor to Screen: 140 pF/m
INSULATION	PVC RoHS Flame Retardant (AS/NZS 3808) Ø = 1.35±0.05 mm*6 Colour: Red, Blue, White, Black, Green, Yellow Thickness: 0.3mm±0.05mm Voltage Rating: 300V
SHIELD	Overall Aluminium / Polyester Laminate Tape Drain Wire: 7*0.20mm Stranded Tinned Copper
OUTER JACKET	PVC RoHS Compliant 75°C PVC to AS3808, Flame Retardant Colour: Grey (RAL:7001) Thickness: 0.76±0.05mm
NOMINAL O.D (mm)	Ø = 5.40mm±0.10mm
PACKAGING	100M Plastic Reel 300M Reel-in-a-Box
CABLE MARKING	MASER SECURITY SOLUTIONS 6CORE SCR DATA CABLE 0.22mm² TCW ACA3166 SECURITY CABLE EXTRA LOW VOLTAGE DD/MM/YYYY 001M-100M-300M



Maser Communications products are approved and meet the GREENSTAR "Best Practice PVC" criteria as set out by the Green Building Council of Australia (GBCA). BUREAU VERATIS CoC No:2821 7/8/2019. As part of this commitment to reduce the environmental impact of PVC material, Maser Communications will aid in the process of recycling any of their relevant product that has reached end of life. For further information on this process please contact us.

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

