

RG-6/U Dual Shield Coax Sky Approved

75ohm, Solid Bare Copper Covered Steel, Gas-injected FPE - Foam Polyethylene, Aluminium Foil-Polyester Tape-Aluminium Foil (100%) Aluminium Braid (60%), Perfect Guard Grease-free Corrosion Protection, PVC - Polyvinyl Chloride, Sunlight Resistant, Black or White Jacket.



Coax Type	Jacket Colour	Drum Size	Maser Code
RG6/U	Black	152m	B1829AC-10-152P
RG6/U	Black	305m	B1829AC-10P
RG6/U	White	152m	B1829AC-9-152P
RG6/U	White	305m	B1829AC-9P

RG-6/U Quad Shield Coax For MATV

75ohm, Solid Bare Copper Covered Steel, Gas-injected FPE - Foam Polyethylene, Aluminium Foil-Polyester Tape-Aluminium Foil (100%), Aluminium Braid (60%), Aluminium Foil-Polyester Tape-Aluminium Foil (100%), Aluminium Braid (40%), PVC - Polyvinyl Chloride, UV Resistant Black Jacket. **Direct Burial** is flooded with Core Guard® II Grease and has a PE - Polyethylene Jacket.



Coax Type	Install Area	Drum Size	Maser Code
RG6/U	Indoor	305m / Cut	B1189AS
RG6/U	Direct Burial	305m / Cut	B1190A

RG-11/U Dual Shield Coax For MATV

75ohm, Solid Bare Copper Covered Steel, Gas-injected FPE - Foam Polyethylene, Aluminium Foil-Polyester Tape-Aluminium Foil (100%) Aluminium Braid (60%), Black PVC - Polyvinyl Chloride, UV Resistant, Black Jacket. **Direct Burial** is flooded with Core Guard® II Grease and has a PE - Polyethylene Jacket.



Coax Type	Install Area	Drum Size	Maser Code
RG11/U	Indoor	305m / Cut	B1523A
RG11/U	Direct Burial	305m / Cut	B1525A

RG-11/U Quad Shield Coax For MATV

75ohm, Solid Bare Copper Covered Steel, Gas-injected FPE - Foam Polyethylene, Aluminium Foil-Polyester Tape-Aluminium Foil (100%), Aluminium Braid (60%), Aluminium Foil-Polyester Tape-Aluminium Foil (100%), Aluminium Braid (40%), PVC - Polyvinyl Chloride, UV Resistant Black Jacket. **Direct Burial** is flooded with Core Guard® II Grease and has a PE - Polyethylene Jacket.



Coax Type	Install Area	Drum Size	Maser Code
RG11/U	Indoor	305m / Cut	B1617A
RG11/U	Direct Burial	305m / Cut	B1618A

HDSI Precision Video Coax For HDTV

100% sweep tested 5 MHz to 4.5 GHz. 75ohm, Solid Bare Copper Conductor, Gas-injected FHDPE - Foam High Density Polyethylene Insulation, Aluminium Foil-Polyester Tape-Aluminium Foil (100%) + Tinned Copper Braid (95 %) Shield, PVC - Polyvinyl Chloride Black Jacket.



Coax Type	Install Area	Drum Size	Maser Code
RG59/U	Indoor	305m / Cut	B1505A
RG6/U	Indoor	305m / Cut	B1694A