

GARDEN LIGHTING CABLE

EXTRA LOW VOLTAGE CABLE



2 Core Garden Lighting Cable

- Figure 8 Parallel Webbed, Stranded Tinned Copper Wire, UV Resistant V90HT PVC, Direct Bury



	1.0mm ²	1.5mm ²	4.0mm ²	6.0mm ²
Product Code	MGL23202 100M	MGL230025 100M	MGL212702 100M	MGL219202 100M
Conductor	Tinned Copper Stranded (32/0.2) 0.20mm +/- 0.003mm	Tinned Copper Stranded (30/0.25) 0.25mm +/- 0.003mm	Tinned Copper Stranded (127/0.2) 0.20mm +/- 0.003mm	Tinned Copper Stranded (192/0.2) 0.20mm +/- 0.003mm
Insulation	UV Resistant V90HT Black PVC With permanent raised rib on one leg.	UV Resistant V90HT Black PVC With permanent raised rib on one leg.	UV Resistant V90HT Black PVC With permanent raised rib on one leg.	UV Resistant V90HT Black PVC With permanent raised rib on one leg.
Insulation Thickness	0.6mm +/- 0.05mm	1.1mm +/- 0.5mm	1.0mm +/- 0.5mm	1.0mm +/- 0.5mm
Packaging	100M Strong Wooden Reel	100M Strong Wooden Reel	100M Strong Wooden Reel	100M Strong Wooden Reel
Nominal O.D (mm)	2.6mm x 5.7mm	4.0mm x 8.3mm	4.70mm x 9.5mm	5.5mm x 11.5mm

EXTRA LOW VOLTAGE – NOT FOR MAINS CONNECTION