


Multicore Security Cable

Stranded Tinned Oxygen Free Copper Wire (AS1125), Flame Retardant PVC Insulation (AS/NZS 3808), Flame Retardant PVC Jacket (AS3808).



Cores	Nominal Area (mm ²)	Length	Maser Code
4 Core	0.22 (7/0.2)	100m Drum	MSEC 4072/100TCW
		100m Box	MSEC 4072/100TCWBX
		300m Box	MSEC 4072/300TCW
4 Core	0.44 (14/0.2)	100m Drum	MSEC 4142/100TCW
		100m Box	MSEC 4142/100TCWBX
		300m Box	MSEC 4142/300TCW
6 Core	0.22 (7/0.2)	100m Drum	MSEC 6072/100TCW
		100m Box	MSEC 6072/100TCWBX
		300m Box	MSEC 6072/300TCW
6 Core	0.44 (14/0.2)	100m Drum	MSEC 6142/100TCW
		100m Box	MSEC 6142/100TCWBX
		300m Box	MSEC 6142/300TCW
8 Core	0.44 (14/0.2)	100m Drum	MSEC 8142/100TCW
		100m Box	MSEC 8142/100TCWBX
		250m Box	MSEC 8142/250TCW

LSZH Low Smoke Security Cable

Stranded Tinned Oxygen Free Copper Wire (AS1125), Low Smoke Zero Halogen (LSZH) Insulation (HFS-90-TP to AS3808), LSZH Jacket (HFS-90-TP to AS3808).

Cores	Nominal Area (mm ²)	Length	Maser Code
4 Core	0.44 (14/0.2)	300m Box	MSEC 4142/300 TCW LSZH
6 Core	0.44 (14/0.2)	300m Box	MSEC 6142/300 TCW LSZH
8 Core	0.44 (14/0.2)	250m Box	MSEC 8142/250 TCW LSZH

CAT6 & CAT6A IP Camera Cable

100% Copper Conductors, 23 AWG, Solid Copper. Cat6 certified for ISO/IEC11801, TIA/EIA568B, YD/T1019-2001. Cat6a certified for ISO/IEC11801, TIA/-568-C.2, HD Base-T Video Streaming.



Category	Speed	Install Area	Outer Jacket	Shielding	Armour	Length	Maser Code	
CAT6 UTP	250Mhz	Internal	Green PVC	-	-	305m Box	MSEC C64P GREEN	
			Yellow PVC	-	-	305m Box	MSEC C64P YELLOW	
			Violet PVC	-	-	305m Box	MSEC C64P VIOLET	
			White LSZH	-	-	305m Drum	MSEC C64P LSZH WHITE	
CAT6 UTP	250Mhz	Direct Bury (Gel)	Black PE	-	-	250m Drum	MSEC C64PEXTGEL/250	
			Black LSZH	-	-	500m Drum	MSEC C64PEXTGEL/500	
			Fire Rated (90Min.)	-	-	Per Metre	C-CAT6UTP4P23FR	
CAT6 FTP	250Mhz	Internal	White PVC	Overall Foil Shield	-	305m Drum	MSEC C64PFTP WHITE	
			External (Dry)	Black PE	Overall Foil Shield	-	250m Drum	MSEC C64PFTPEXT 250M
				Black PE	Overall Foil Shield	-	500m Drum	MSEC C64PFTPEXT 500M
CAT6A U/FTP	500Mhz	Internal	White LSZH + Black PVC	Overall Foil Shield	SWA	Per Metre	BEL145007	
			White PVC	Individual Foil Shield	-	305m Drum	MSEC C6A4PUFTP WHITE	

Shielded Muticore Security Cable

Stranded Tinned Oxygen Free Copper Wire (AS1125), Flame Retardant PVC Insulation (AS/NZS 3808), Overall Foil Shield, Flame Retardant Jacket (AS3808).



Cores	Nominal Area (mm ²)	Length	Maser Code
6 Core	0.22 (7/0.2)	100m Drum	MSEC 6072SCR/100 TCW
		300m Box	MSEC 6072SCR/300 TCW
7 Core	0.44 (14/0.2)	100m Drum	MSEC 7142SCR/100 TCW
		250m Box	MSEC 7142SCR/250 TCW

Fig.8 Low Voltage Power Cable

2 Core, Figure 8 / Parallel Webbed, Stranded Oxygen Free Plain Copper Wire (AS1125), V90 PVC Insulation (AS3191), AC50V / DC 120V (AS/NZS 3000:2000).



Cores	Nominal Area (mm ²)	Length	Maser Code
2 Core	1.13 (6/0.3)	100m	AU-AFE216030 100M
		500m	AU-AFE216030 500M
		100m	AU-AFE226030 100M
		500m	AU-AFE226030 500M
2 Core TINNED	1.84 (26/0.3)	250m	AU-MFE226030 250M
		500m	AU-MFE226030 500M