

## 2 Core Black Speaker Cable

2 Core, Figure 8 / Parallel Webbed, Stranded Oxygen Free Plain Copper Wire (AS1125), Black V75 PVC Insulation (AS/NZS 3808) with Red Stripe.



| Nominal Area (mm <sup>2</sup> ) | Length | Maser Code           |
|---------------------------------|--------|----------------------|
| 0.50                            | 100m   | MSEC SPK216020/100BR |
| 0.50                            | 500m   | MSEC SPK216020/500BR |
| 0.75                            | 100m   | MSEC SPK224020/100BR |
| 0.75                            | 500m   | MSEC SPK224020/500BR |

## 2 Core Clear Speaker Cable

2 Core, Figure 8 / Parallel Webbed, Stranded Oxygen Free Plain Copper Wire, UV Stabilised V90 PVC (AS/NZS 3808:2000), Clear with Red Stripe.



| Nominal Area (mm <sup>2</sup> ) | Length | Maser Code        |
|---------------------------------|--------|-------------------|
| 0.75                            | 100m   | AU-FSC224020 100M |
| 0.75                            | 500m   | AU-FSC224020 500M |
| 2.0                             | 100m   | AU-FSC264020 100M |
| 2.0                             | 500m   | AU-FSC264020 500M |

## 2 Core Violet High-Flex Speaker Cable

Stranded Oxygen Free Plain Copper wire (AS1125), Red/Black V75 PVC Insulation (AS/NZS 3808), Violet Flame Retardant PVC Jacket (HBZRH-80FZW). **100V Line Rated**

- Easy Pull – Reel in a Box
- Metre Marked



| Nominal Area (mm <sup>2</sup> ) | Length | Conductor No./Dia. (mm <sup>2</sup> ) | Colour | Maser Code           |
|---------------------------------|--------|---------------------------------------|--------|----------------------|
| 1.3                             | 100m   | 65/0.16                               | Violet | MSEC SPK265016/100P  |
| 1.3                             | 250m   | 65/0.16                               | Violet | MSEC SPK265016/250P  |
| 2.1                             | 100m   | 105/0.16                              | Violet | MSEC SPK2105016/100P |
| 2.1                             | 250m   | 105/0.16                              | Violet | MSEC SPK2105016/250P |

## 2 Core Black High-Flex Speaker Cable

Stranded Oxygen Free Plain Copper wire (AS1125), Red/Black V75 PVC Insulation (AS/NZS 3808), Violet Flame Retardant PVC Jacket (HBZRH-80FZW). **100V Line Rated**

- Easy Pull – Reel in a Box
- Metre Marked



| Nominal Area (mm <sup>2</sup> ) | Length | Conductor No./Dia. (mm <sup>2</sup> ) | Colour | Maser Code           |
|---------------------------------|--------|---------------------------------------|--------|----------------------|
| 1.3                             | 100m   | 65/0.16                               | Black  | MSEC SPK265016/100B  |
| 2.1                             | 100m   | 105/0.16                              | Black  | MSEC SPK2105016/100B |

## 4 Core High-Flex Speaker Cable

Stranded Oxygen Free Plain Copper wire (AS1125), Red/Black/Green/White V75 PVC Insulation (AS/NZS 3808), Violet Flame Retardant PVC Jacket (HBZRH-80FZW) **100V Line Rated**

- Easy Pull – Reel in a Box
- Metre Marked



| Nominal Area (mm <sup>2</sup> ) | Length | Conductor No./Dia. (mm <sup>2</sup> ) | Colour | Maser Code           |
|---------------------------------|--------|---------------------------------------|--------|----------------------|
| 1.3                             | 100m   | 65/0.16                               | Violet | MSEC SPK465016/100P  |
| 1.3                             | 250m   | 65/0.16                               | Violet | MSEC SPK465016/250P  |
| 2.1                             | 100m   | 105/0.16                              | Violet | MSEC SPK4105016/100P |
| 2.1                             | 250m   | 105/0.16                              | Violet | MSEC SPK4105016/250P |

## 4 Core High-Flex Speaker Cable

Stranded Oxygen Free Plain Copper wire (AS1125), Red/Black/Green/White V75 PVC Insulation (AS/NZS 3808), Violet Flame Retardant PVC Jacket (HBZRH-80FZW) **100V Line Rated**

- Easy Pull – Reel in a Box
- Metre Marked



| Nominal Area (mm <sup>2</sup> ) | Length | Conductor No./Dia. (mm <sup>2</sup> ) | Colour | Maser Code           |
|---------------------------------|--------|---------------------------------------|--------|----------------------|
| 1.3                             | 100m   | 65/0.16                               | Black  | MSEC SPK465016/100B  |
| 2.1                             | 100m   | 105/0.16                              | Black  | MSEC SPK4105016/100B |