

MAS1PHVAC

1 Pair 18awg (0.8mm) BMS/HVAC Control Cable

EXTRA LOW VOLTAGE – NOT FOR MAINS CONNECTION



Part number	MAS1PHVAC
Pair Count	1 Pair
Conductor	Tinned Copper Wire
Size	18awg (0.8mm)
Stranding	7/0.40mm
Insulation	PVC
Insulation Thickness	0.25mm ± 0.03mm
Pair Identification	Black/White
Outer Jacket Sheath	PVC
Outer Jacket Sheath Thickness	0.50mm ± 0.03mm
Overall Diameter (nominal)	4.40mm ± 0.15mm
Colour	Blue
Temperature Rating °C	-20°C to +75°C
Nom. Capacitance Cond. To Cond. pF/m	171.42
Nom. Cond DC Resistance Ω/km @ 20°C	21.351
Max. Operating Voltage - UL	300v RMS
Metre Marking	001m – 500m
Weight kg/305m	11.0
Packaging	500m Drum
RoHS compliant	Yes

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.